

## DS-KIS901-P Facial Network Intercom Bundle



- MinMoe face recognition terminal and indoor station bundle for villa or commercial
- One call button for easier calls
- Supports Wi-Fi and PoE power supply for easy installation
- Including: DS-K1T341AM × 1, DS-KH8350-WTE1 × 1, PSU × 2, 16GB TF card × 1
- Power adapter included in the package

## ▪ Specification

| Face Recognition Terminal |   |
|---------------------------|---|
| <b>System parameters</b>  |   |
| Operation system          | Embedded Linux operation system               |
| <b>Authentication</b>     |   |
| Card type                 | M1 card                                       |
| Card reading distance     | 0 to 3 cm                                     |
| Card reading duration     | < 1 s   |
| Face recognition duration | < 0.2 s                                       |
| Face recognition distance | 0.3 to 1.5 m                                  |
| <b>General</b>            |   |
| Protection level          | IP65  |
| Power supply              | 12 VDC, 2A                                    |
| Working temperature       | -30 °C to 60 °C (-22 °F to 140 °F)            |
| Working humidity          | 0 to 90% (No condensing)                      |
| <b>Function</b>           |   |
| Face antispoofing         | Support                                       |
| Live view                 | Supports live view on the platform, H.264     |
| Face recognition          | Supports face recognition in low illumination |
| Access control management | Support multiple authentication methods       |
| <b>Audio</b>              |   |
| Audio input               | Built-in omnidirectional microphone           |
| Audio output              | Built-in loudspeaker                          |
| Volume adjustment         | Adjust via device or client                   |
| <b>Network</b>            |   |
| Wired network             | 10/100/1000 Mbps self-adaptive                |
| Communication protocol    | ISUP 5.0                                      |
| <b>Camera</b>             |   |
| Pixel                     | 2 MP  |
| WDR                       | Support                                       |
| Lens                      | 2   |
| Video standard            | PAL (Default) and NTSC                        |
| <b>Screen</b>             |   |
| Size                      | 4.3-inch                                      |
| Resolution                | 800 × 480                                     |
| Operation method          | Capacitive touch screen                       |
| <b>Interfaces</b>         |   |
| Network interface         | 1, RJ45                                       |
| RS-486                    | 1   |
| Wiegand                   | Wiegand 26 and Wiegand 34                     |
| Lock output               | 1   |
| Exit button               | 1   |
| Door contact input        | 1   |
| Power interface           | 1   |
| TAMPER switch             | 1   |

|                            |   |
|----------------------------|---|
| USB                        | 1, USB 2.0  |
| <b>Capacity</b>            |   |
| Card capacity              | 1500  |
| Face capacity              | 1500  |
| Event capacity             | 150000  |
| <b>Indoor station</b>      |   |
| <b>System parameters</b>   |   |
| Operation system           | Embedded Linux operation system                     |
| Memory                     | 128 MB  |
| Flash                      | 32 MB   |
| <b>Display parameters</b>  |   |
| Display screen             | 7-inch colorful IPS LCD                             |
| Display resolution         | 1024 × 600  |
| Operation method           | Capacitive touch screen, physical button            |
| <b>Audio parameters</b>    |   |
| Audio input                | Built-in omnidirectional microphone                 |
| Audio output               | Built-in loudspeaker                                |
| Audio quality              | Noise suppression and echo cancellation             |
| Audio compression standard | G.711 U   |
| Audio compression Rate     | 64 Kbps   |
| <b>Network parameters</b>  |   |
| Wired network              | 10/100 Mbps self-adaptive                           |
| Wireless network           | Wi-Fi 802.11 b/g/n                                  |
| Protocol                   | TCP/IP, SIP, RTSP                                   |
| Network interface          | 1 RJ-45 10/100 Mbps self-adaptive                   |
| Alarm input                | 8-ch alarm inputs                                   |
| I/O output                 | 2   |
| TF card                    | Max to 32 G, SD 2.0 or lower version                |
| <b>General</b>             |   |
| Power supply               | IEEE802.3af, standard PoE<br>12 VDC/1 A             |
| Power consumption          | ≤ 7 W   |
| Working temperature        | -10 °C to 55 °C (14 °F to 131 °F)                   |
| Working humidity           | 10% to 90%  |
| Dimension (L x W x H)      | 180 mm × 140 mm × 22.4 mm (7.09" × 5.51" × 0.88")   |
| Power supply via detector  | 12 V, 200 mA  |
| Weight                     | 899 g (with packaging)<br>355 g (without packaging) |

## ▪ Available Model

DS-KIS901-P

**Headquarters**

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
www.hikvision.com



Follow us on social media to get the latest product and solution information.

